



Polias: Diâmetro mínimo recomendado (mm)

Tipo de Correia	Tensão Máxima Recomendada %								
	60% até 100%			30% até 60% Factor de Segurança > 17			Até 30% Factor de Segurança > 33		
	A	B	C	A	B	C	A	B	C
250/2	250	200	160	200	160	125	160	160	125
315/2	250	200	160	200	160	125	160	160	125
400/3	315	250	200	250	200	160	200	200	160
500/3	400	315	250	315	250	200	250	250	200
500/4	500	400	315	400	315	250	315	315	250
630/3	500	400	315	400	315	250	315	315	250
630/4	500	400	315	400	315	250	315	315	250
800/3	630	500	400	500	400	315	400	400	315
800/4	630	500	400	500	400	315	400	400	315
1000/3	630	500	400	500	400	315	400	400	315
1000/4	800	630	500	630	500	400	500	500	400
1000/5	800	630	500	630	500	400	500	500	400
1250/3	800	630	500	630	500	400	500	500	400
1250/4	1000	800	630	800	630	500	630	630	500
1250/5	1000	800	630	800	630	500	630	630	500
1600/4	1000	800	630	800	630	500	630	630	500
1600/5	1250	1000	800	1000	800	630	800	800	630
2000/4	1250	1000	800	1000	800	630	800	800	630
2000/5	1250	1000	800	1000	800	630	800	800	630
2500/5	1600	1250	1000	1250	1000	800	1000	1000	800
3150/6	2000	1600	1250	1600	1250	1000	1250	1250	1000

A = Tambor Motriz ;
 B = Tambor Mandado;
 C = Polias Tensoras,